BF STRETCH CAD CAM



PRODUCT DESCRIPTION

The BF STRETCH series is super-elastic covering polyurethane products suitable for thermal transfer on elastic fabrics such as LYCRA® and ideal for sports and technical garments.

The cutting line of all the films is highly visible and the workability of the product is unique. The polyester carrier is not adhesive and quick weeding.

The thickness of only 65 microns and its elasticity make the BF STRETCH series pleasant to the touch and conformable on any fabric. It is resistant to washing up to 60°C.

APPLICATION TECHNIQUES

Knockout

APPLICATION STEPS


- Cut 45° blade •
- Weed excess material
- Turn on your heat press heat to 140°C/285°F •
- Place your graphic on the garment •
- Press it 140°C/285°F for 10 seconds •
- Remove the liner cold •

SIZES

H 50 cm	L 25 mt / 12,5 mt / 5 mt / 1 mt
H 75 cm	L 25 mt (upon request)
H 100 cm	L 25 mt (upon request)
H 150 cm	L 25 mt (upon request)

Comply with regulation REACH n°1907/2006/EU

TECHNICAL DATA



Thickness: 65µ (±5%)

Finish: matte

PLOTTER SETTING



Cut settings: mirror

Blade: 45°



Minimum cut: 1 cm

APPLICATION

follow us

Temperature: 140°C - 285°F Time: 10" Liner removal: cold Pressure: medium - 3,5 bar - 50 PSI Textile: stretch fabrics, synthetic, mixed

WASH RESISTANCE

First wash after application	wait 12 hours
Wash insideout	
Max wash temperature	60°C - 104°F
Dry clean	×
Dryer	\checkmark

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev_2024/06

BF STRETCH



COLOUR GUIDE

• Suitable for elastic fabrics

• Easy to weed





BF H792NA GOLD STRETCH



BF H796NA SILVER STRETCH

BF H730NA E



BF H740NA ROYAL BLUE STRETCH



BF H748NA NAVY BLUE STRETCH





<image>